

## ALVIER

SHOES - Safety

Ref. ALV - Size: 38 to 48

EN ISO 20345: 2011 S3 WR CI HRO SRC



The PPE Specialist

### PRODUCT PHOTOS



1.11 kg



### UNISEX MODEL



### DESCRIPTION

The Alvier is a trekking-type high safety shoe. It features a Vibram® anti-perforation composite sole, a waterproof-breathable eVent® inner lining and a Perwanger® leather upper with polyamide laces. Rugged, they feature a rubber side stone guard.

### 3 MAIN BENEFITS

- **Vibram®**: These soles are made of an advanced rubber offering **unrivalled grip**, waterproofing and **optimum comfort**.
- **eVent®**: This **waterproof** membrane resists moisture and water molecules thanks to a direct ventilation system. Moisture wicks away from the fabric and prevents water from penetrating inside. This material helps users **stay dry** and **comfortable** when wearing it.

- **Perwanger®**: This **water-repellent leather** prevents water from seeping in, while ensuring the leather's **breathability**. Due to special tanning techniques this leather **resists abrasions** even on rocky terrain and **ensures longevity**.

### WEIGHTS & DIMENSIONS

Size: 42  
 Weight: 2.22 kg  
 Front Height: 18 cm

### PACKAGING

Alvier's packaging is made of cardboard with **CITEO** standardization.

Donner ensemble une nouvelle vie à nos produits.

# ALVIER

SHOES - Safety

Ref. ALV - Size: 38 to 48

For resellers,  
order on B2B



**EN ISO 20345:2011 S3 WR CI HRO SRC**

## TECHNICAL SPECS



Double-riveted lacing hooks

Perwanger® 2.2 – 2.4mm water-repellent cowhide upper and gusset

Event® Direct Venting™ membrane sock lining

Edge blocking middle shoe

Flat D-eyelets

Ball-bearing grommets

Heel counter

Aluminum Protective Shell

Lug shoe addition of studs

Rubber stone guards

Bi-density midsole

Anti-slip Vibram® sole, resistant to 300°C, oils and hydrocarbons

Antifungal and antibacterial primer

Composite anti-perforation sole

## STANDARD EN ISO 20345:2011



**200 J toe cap:** forefoot protection against impact and crushing



**Non-slip tread** on detergent-and-watercoated ceramic and glycerine-coated steel floors



**Antistatic**



**Heel shock absorption**



**Resistance of entire shoe to water penetration and absorption**



**Oil-hydrocarbon sole resistance**



**Cold insulation (-17°C)**



**300°C resistant sole**



**Shoe upper resistance to water penetration and absorption**



**Anti-puncture insert 1100 N:** foot protection against perforation

## COMPLIANCE

**CE** 037222302/OI  
Issued by a notified body 0498



**SOLIDUR SAS**

335, Impasse Teractive Ouest - ZA Teractive - 50140 Romagny-Fontenay, FRANCE  
Tél. +33 (0)2 33 59 45 12

[www.solidur.fr](http://www.solidur.fr) @solidurfrance

